Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

## Inoxline H5 / H10 / H15 / H20

Revision date: 30/11/2018

Version: 2.1

Date of issue: 27/06/2015 Supersedes: 01/03/2017 SDS reference: LAT-H2-AR-002





Danger

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

4.4. Due du et identifien	
1.1. Product identifier	
Trade name	: Inoxline H5 / H10 / H15 / H20
SDS no	: LAT-H2-AR-002
1.2. Relevant identified uses of the substance of	or mixture and uses advised against
Relevant identified uses	: Industrial and professional. Perform risk assessment prior to use. Contact supplier for more information on uses.
Uses advised against	: Consumer use.
1.3. Details of the supplier of the safety data sh	leet
Company identification	: Elme Messer L
	Katlakalna iela 9
	LV-1073 Rīga Latvija
	00371 67355445
	www.elmemesser.lv
	eml@eml.lv
1.4. Emergency telephone number	
Emergency telephone number	: 112 (24h) Elme Messer L +371 67355445

# **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]			
Physical hazards	Flam. Gas 1	H220	Calculation method
	Press. Gas (Comp.)	H280	Calculation method

Full text of H-statements see section 16.

### 2.2. Label elements

00371 67355445

Labelling according to Regulation	on (EC) No. 127	2/2008 [CLP]		
Hazard pictograms (CLP)	:	GHS02 GH	504	
Signal word (CLP)	:	Danger		
Hazard statements (CLP)       : H220 - Extremely flammable gas         H280 - Contains gas under pressure; may explode if heated				
Precautionary statements (CLP)				
	- Prevention :	P210 - Keep away from smoking	heat, hot surfaces, sparks, open flames and other igni	tion sources. No
	- Response	P377 - Leaking gas fire:	Do not extinguish, unless leak can be stopped safely.	
Elme Messer L Katlakalna iela 9 LV-1073 Rīga Latvija		EN (English)	SDS Ref.: LAT-H2-AR-002	1/9

# **ELME MESSER G/4/S**

SDS Ref.: LAT-H2-AR-002

P381 - In case of leakage, eliminate all ignition sources.. - Storage : P403 - Store in a well-ventilated place..

#### 2.3. Other hazards

: None.

## **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances : Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Argon	(CAS-No.) 7440-37-1 (EC-No.) 231-147-0 (EC Index-No.) (REACH-no) *1	balance	Press. Gas (Comp.), H280
Hydrogen	(CAS-No.) 1333-74-0 (EC-No.) 215-605-7 (EC Index-No.) 001-001-00-9 (REACH-no) *1	5 - 20	Flam. Gas 1, H220 Press. Gas (Comp.), H280

Full text of H-statements: see section 16

Contains no other components or impurities which will influence the classification of the product.

\*1: Listed in Annex IV / V REACH, exempted from registration.

\*2: Registration deadline not expired.

\*3: Registration not required: Substance manufactured or imported < 1t/y.

### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

- Ingestion	: Ingestion is not considered a potential route of exposure.
- Eye contact	: Adverse effects not expected from this product.
- Skin contact	: Adverse effects not expected from this product.
- Inhalation	: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.

### 4.2. Most important symptoms and effects, both acute and delayed

: Refer to section 11.

### 4.3. Indication of any immediate medical attention and special treatment needed

: None.

### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

- Suitable extinguishing media	: Water spray or fog.
- Unsuitable extinguishing media	: Carbon dioxide. Do not use water jet to extinguish.

SDS Ref.: LAT-H2-AR-002

5.2. Special hazards arising from the substance or mixture		
Specific hazards Hazardous combustion products	<ul><li>Exposure to fire may cause containers to rupture/explode.</li><li>None.</li></ul>	
5.3. Advice for firefighters		
Specific methods	<ul> <li>Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.</li> <li>If possible, stop flow of product.</li> <li>Use water spray or fog to knock down fire fumes if possible.</li> <li>Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive reignition may occur. Extinguish any other fire.</li> <li>Move containers away from the fire area if this can be done without risk.</li> </ul>	
Special protective equipment for fire fighters	<ul> <li>In confined space use self-contained breathing apparatus. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask. Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.</li> </ul>	

# **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

:	Act in accordance with local emergency plan. Try to stop release.
	Evacuate area. Monitor concentration of released product.
	Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.
	Consider the risk of potentially explosive atmospheres. Eliminate ignition sources.
	Ensure adequate air ventilation. Prevent from entering sewers, basements and workpits, or any place where its accumulation
	can be dangerous. Stay upwind.
:	Try to stop release.

## 6.3. Methods and material for containment and cleaning up

: Ventilate area.

## 6.4. Reference to other sections

6.2. Environmental precautions

: See also sections 8 and 13.

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

ELME MESSER GAAS

# Inoxline H5 / H10 / H15 / H20

SDS Ref.: LAT-H2-AR-002

Safe use of the product :	Assess the risk of potentially explosive atmospheres and the need for explosion-proof equipment. Purge air from system before introducing gas. Take precautionary measures against static discharge. Keep away from ignition sources (including static discharges). Consider the use of only non-sparking tools. Ensure equipment is adequately earthed. The product must be handled in accordance with good industrial hygiene and safety procedures. Only experienced and properly instructed persons should handle gases under pressure. Consider pressure relief device(s) in gas installations. Ensure the complete gas system was (or is regularily) checked for leaks before use. Do not smoke while handling product. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Avoid suck back of water, acid and alkalis. Do not breathe gas. Avoid release of product into atmosphere.		
Safe handling of the gas receptacle :	Refer to supplier's container handling instructions. Do not allow backfeed into the container. Protect cylinders from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Close container valve after each use and when empty, even if still connected to equipment. Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the cylinder contents. Suck back of water into the container must be prevented. Open valve slowly to avoid pressure shock.		
7.2. Conditions for safe storage, including any incompatibilities			
	Observe all regulations and local requirements regarding storage of containers. Containers should not be stored in conditions likely to encourage corrosion. Container valve guards or caps should be in place. Containers should be stored in the vertical position and properly secured to prevent them from falling over. Stored containers should be periodically checked for general condition and leakage. Keep container below 50°C in a well ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials. Segregate from oxidant gases and other oxidants in store. All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere.		
7.3. Specific end use(s)			

: None.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

OEL (Occupational Exposure Limits) : No data available.

DNEL (Derived-No Effect Level) : No data available.

PNEC (Predicted No-Effect Concentration) : No data available.

SDS Ref.: LAT-H2-AR-002

#### 8.2. Exposure controls

8.2.1. Appropriate engineering controls : Provide adequate general and local exhaust ventilation. Product to be handled in a closed system. Systems under pressure should be regularily checked for leakages. Ensure exposure is below occupational exposure limits (where available). Gas detectors should be used when flammable gases/vapours may be released. Consider the use of a work permit system e.g. for maintenance activities. 8.2.2. Individual protection measures, e.g. personal protective equipment : A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected. Wear safety glasses with side shields. · Eye/face protection Standard EN 166 - Personal eye-protection - specifications Skin protection - Hand protection : Wear working gloves when handling gas containers. Standard EN 388 - Protective gloves against mechanical risk. - Other Consider the use of flame resistant anti-static safety clothing. Standard EN ISO 14116 - Limited flame spread materials. Standard EN 1149-5 - Protective clothing: Electrostatic properties. Wear safety shoes while handling containers. Standard EN ISO 20345 - Personal protective equipment - Safety footwear. · Respiratory protection Gas filters may be used if all surrounding conditions e.g. type and concentration of the contaminant(s) and duration of use are known. Use gas filters with full face mask, where exposure limits may be exceeded for a short-term period, e.g. connecting or disconnecting containers. Gas filters do not protect against oxygen deficiency. Standard EN 14387 - Gas filter(s), combined filter(s) and standard EN136, full face masks . Thermal hazards : None in addition to the above sections 8.2.3. Environmental exposure controls

: Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Appearance
------------

Physical state at 20°C / 101.3kPa	: Gas.
Colour	: Mixture contains one or more component(s) which have the following colour(s): Colourless.
Odour	: Odourless.
Odour threshold	: Odour threshold is subjective and inadequate to warn of overexposure.
pH value	: Not applicable for gases and gas mixtures.
Molar mass	: Not applicable for gas mixtures.
Melting point	: Not applicable for gas mixtures.
Boiling point	: Not applicable for gas mixtures.
Flash point	: Not applicable for gases and gas mixtures.
Evaporation rate (ether=1)	: Not applicable for gases and gas mixtures.
Flammability range	: Flammability range not available.
Vapour pressure [20°C]	: Not applicable.

## ELME MESSER GAAS

# Inoxline H5 / H10 / H15 / H20

SDS Ref.: LAT-H2-AR-002

Vapour pressure [50°C]	: Not applicable.
Relative density, gas (air=1)	: Heavier than air.
Solubility in water	: No data available
Partition coefficient n-octanol/water [log Kow]	: Not applicable for gas mixtures.
Auto-ignition temperature	: Not known.
Decomposition point [°C]	: Not applicable.
Viscosity [20°C]	: No reliable data available.
Explosive Properties	: Not applicable.
Oxidising Properties	: Not applicable.
9.2. Other information	
Other data	: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

SECTION 10: Stability and reactivity	у
10.1. Reactivity	
10.2. Chemical stability	: No reactivity hazard other than the effects described in sub-sections below.
10.3. Possibility of hazardous reactions	: Stable under normal conditions.
	: Can form explosive mixture with air. May react violently with oxidants.
10.4. Conditions to avoid	: Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid moisture in installation systems.
10.5. Incompatible materials	
	: Air, Oxidisers. For additional information on compatibility refer to ISO 11114.
<u>10.6. Hazardous decomposition products</u>	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# **SECTION 11: Toxicological information**

11.1. Information on toxicological effects	
Acute toxicity	: Toxicological effects not expected from this product if occupational exposure limit values are not exceeded.
Skin corrosion/irritation	: No known effects from this product.
Serious eye damage/irritation	: No known effects from this product.
Respiratory or skin sensitisation	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Toxic for reproduction : Fertility	: No known effects from this product.
Toxic for reproduction : unborn child	: No known effects from this product.
STOT-single exposure	: No known effects from this product.
STOT-repeated exposure	: No known effects from this product.
Aspiration hazard	: Not applicable for gases and gas mixtures.

SDS Ref.: LAT-H2-AR-002

SECTION 12: Ecological informati	on
<u>12.1. Toxicity</u>	
Assessment	: No ecological damage caused by this product.
12.2. Persistence and degradability	
Assessment	. No ecological damage caused by this product
Assessment 12.3. Bioaccumulative potential	: No ecological damage caused by this product.
Assessment 12.4. Mobility in soil	: No data available.
Assessment	: Because of its high volatility, the product is unlikely to cause ground or water pollution. Partition into soil is unlikely.
12.5. Results of PBT and vPvB assessmer	<u>nt</u>
Assessment	: Not classified as PBT or vPvB.
12.6. Other adverse effects	
	: No known effects from this product.
Effect on the ozone layer	: None.
Effect on global warming	: Contains greenhouse gas(es).
SECTION 13: Disposal considerat	ions
13.1. Waste treatment methods	
	Contact supplier if guidance is required. Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded. Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at http://www.eiga.eu for more guidance on suitable disposal methods. Return unused product in original cylinder to supplier.
List of hazardous waste codes (from Commission Decision 2000/532/EC as amended)	: 16 05 04 *: Gases in pressure containers (including halons) containing hazardous substances.
13.2. Additional information	
	: External treatment and disposal of waste should comply with applicable local and/or national regulations
SECTION 14: Transport information	on
<u>14.1. UN number</u>	
UN-No.	: 1954

UN-No. 14.2. UN proper shipping name	: 1954		
Transport by road/rail (ADR/RID)	: COMPRESSED GAS, FLAMMABLE, N.O.S. (Hydrogen, Argon)		
Transport by air (ICAO-TI / IATA-DGR)	: Compressed gas, flammable, n.o.s. (Hydrogen, Argon)		
Transport by sea (IMDG)	: COMPRESSED GAS, FLAMMABLE, N.O.S. (Hydrogen, Argon)		
Elme Messer L Katlakalna iela 9 LV-1073 Rīga Latvija 00371 67355445	EN (English)	SDS Ref.: LAT-H2-AR-002	7/9

SDS Ref.: LAT-H2-AR-002

## 14.3. Transport hazard class(es)

### Labelling



:

2.1 : Flammable gases

Trepoport by read/roll (ADD/DID)	
Transport by road/rail (ADR/RID) Class	: 2
Classification code	: 2 : 1F
Hazard identification number	: 23
Tunnel Restriction	
	: B/D - Tank carriage : Passage forbidden through tunnels of category B, C, D and E. Other carriage : Passage forbidden through tunnels of category D and E
Transport by air (ICAO-TI / IATA-DGR)	
Class / Div. (Sub. risk(s))	: 2.1
Transport by sea (IMDG)	
Class / Div. (Sub. risk(s))	: 2.1
Emergency Schedule (EmS) - Fire	: F-D
Emergency Schedule (EmS) - Spillage	: S-U
14.4. Packing group	
Transport by road/rail (ADR/RID)	: Not applicable
Transport by air (ICAO-TI / IATA-DGR)	: Not applicable
Transport by sea (IMDG)	: Not applicable
14.5. Environmental hazards	
Transport by road/rail (ADR/RID)	: None.
Transport by air (ICAO-TI / IATA-DGR)	: None.
Transport by sea (IMDG)	: None.
14.6. Special precautions for user	
Packing Instruction(s)	
Transport by road/rail (ADR/RID)	: P200
Transport by air (ICAO-TI / IATA-DGR)	
Passenger and Cargo Aircraft	: Forbidden
Cargo Aircraft only	: 200
Transport by sea (IMDG)	: P200
Special transport precautions	<ul> <li>Avoid transport on vehicles where the load space is not separated from the driver's compartment.</li> <li>Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.</li> <li>Before transporting product containers: <ul> <li>Ensure there is adequate ventilation.</li> <li>Ensure that containers are firmly secured.</li> <li>Ensure cylinder valve is closed and not leaking.</li> <li>Ensure valve outlet cap nut or plug (where provided) is correctly fitted.</li> <li>Ensure valve protection device (where provided) is correctly fitted.</li> </ul> </li> </ul>

\_\_\_\_\_

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

: Not applicable.

EU-Regulations	
Restrictions on use	: None.
Seveso Directive : 2012/18/EU (Seveso III)	: Covered.
National regulations	
National legislation	: Ensure all national/local regulations are observed.
Water hazard class (WGK)	: -
15.2. Chemical safety assessment	
	: A CSA does not need to be carried out for this product.

SECTION 16: Other information	
Indication of changes	: Revised safety data sheet in accordance with commission regulation (EU) No 2015/830.
Abbreviations and acronyms	<ul> <li>ATE - Acute Toxicity Estimate. CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008. REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006. EINECS - European Inventory of Existing Commercial Chemical Substances. CAS# - Chemical Abstract Service number. PPE - Personal Protection Equipment. LC50 - Lethal Concentration to 50 % of a test population. RMM - Risk Management Measures. PBT - Persistent, Bioaccumulative and Toxic. vPvB - Very Persistent and Very Bioaccumulative. STOT- SE : Specific Target Organ Toxicity - Single Exposure. CSA - Chemical Safety Assessment. EN - European Standard. UN - United Nations. ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road. IATA - International Air Transport Association. IMDG code - International Maritime Dangerous Goods. RID - Regulations concerning the International Carriage of Dangerous Goods by Rail. WGK - Water Hazard Class.</li> </ul>
Training advice	: Ensure operators understand the flammability hazard.
Further information	<ul> <li>Classification using data from databases maintained by the European Industrial Gases Association (EIGA). Classification in accordance with the calculation methods of Regulation (EC) 1272/2008 CLP.</li> </ul>

## Full text of H- and EUH-statements

Flam. Gas 1	Flammable gases, Category 1
Press. Gas (Comp.)	Gases under pressure : Compressed gas
H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.

#### DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility

and safety study should be carried out. Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

End of document